



Stainer UG

Universal acrylic primer

- Equalizes substrate absorption
- Reinforces the substrate
- Protects against moisture impact

PRODUCT DESCRIPTION

The **Stainer UG** is a universal acrylic primer for priming and equalising absorption of cement, stucco, finishing plaster, brick, drywall, and concrete floor substrates. It effectively reinforces the substrate and prepares the surface for finish painting, decorative plasters, or wallpapers.

SUBSTRATE PREPARATION

The substrate should be dry, stable, and adhesive. That is it should be strong enough and free of any layers that could decrease adhesion, such as dust, dirt, wax, or grease. Thoroughly remove old paint and other poorly adhesive layers. Repair and fill in minor damage (cracks, cavities). Remove, disinfect, and leave to dry any biofilm. Old flaking coats, sandy, chalking, and very absorptive substrates should be first reinforced with the **Stainer TG** water-based primer. The Stainer UG can be applied to fully cured and dry substrates. Stucco curing time –over 14 days, concrete – 28 days, thin mineral plasters – over 7 days.

PRODUCT PREPARATION AND APPLICATION

STAINER UG is delivered ready to use. Do not dilute. Shake the packaging several times before use. Apply with a paint brush or roller or spray a thin, uniform coat. If the substrate remains excessively absorptive after the application, repeat. Apply in the optimum conditions: the substrate, ambient, and product temperature should be from + 5°C to + 25°C.

The drying time depends on the substrate, temperature, and air RH, but generally is about 4 hours. The surface can be considered completely dry after 24 hours. Lower temperatures and higher air humidity affect the drying time.

CONSUMPTION

A single primer coat consumes 0.1 l/m² on average subject to substrate roughness and absorptive characteristics.

TOOL CLEANING

Clean tools with water immediately after use.

PACKAGING

Bottle of 1 l: 12 pieces in a box; bottle of 5 l: 114 pieces on a pallet
 Only completely empty containers can be recycled.

STORAGE

Store and transport the primer in sealed original containers at + 5°C to + 25°C. Do not overheat. The shelf life is 12 months from the date of manufacture on the container.

SUPERVISION

The product quality is monitored by the Production Facility laboratory in accordance with the applicable reference documents and in-house quality control procedures.

SAFETY GUIDELINES

Keep out of reach of children. Read the label before use. Dispose of the content/ container into municipal waste management containers. Comply with general OSH regulations.

SPECIFICATION

Colour	milky
Density	1 g/cm ³
pH	7.5
Substrate and ambient temperature during application	+ 5°C to + 25°C
VOC acc. to Directive 2004/42/EC 30 g/l (2010)	Below 5 g/l
Drying time at 23 ± 2°C and RH 50 ± 5%	about 4 h

ADDITIONAL INFORMATION

The information above is the product description. It should be considered general guidelines based on our research and practical experience, which does not take into account requirements related to a specific application. Therefore, it is recommended to test the product first. Product parameters may slightly change within the declared product class, which does not impact the performance and work with the product. The information provided may not be ground for any compensatory claims.

This data sheet replaces all previous ones. Reference documentation for the product is available at www.stainer.pl